



SERIES ARC300

ESBE®
NO.1 IN HYDRONIC SYSTEM CONTROL

Mtrl.nr: 9814 09 55 • Ritn.nr 8466 vers. A • Rev 1512



Series ARC300

CE





LVD 2006/95/EC valid until April 19th 2016

LVD 2014/35/EU valid from April 20th 2016

EMC 2004/108/EC valid until April 19th 2016


EMC 2014/30/EU valid from April 20th 2016

RoHS 2011/65/EU



Actuator Settings **D**amper Assembly

**D
1A**





Max working range
0° – 90°

**D
1B**

Limiting working range • Clockwise working direction (R/CW)

Example R/CW working range 20°- 70°



ARC368/
ARC369
Dip Switch 4





**E
3**

**D
1C**

Limiting working range • Counter clockwise working direction (L/CCW)

Min working range
45° – 45°



Exampel L/CCW working range 35°- 60°





ARC368/
ARC369
Dip Switch 4




**E
3**

i


9 – 18 mm




9 – 26 mm

i**D2****D3**


R/CW =
Closed (0%) position






Min. 60 mm



L/CCW =
Open (100%) position




Min. 60 mm



**D4**

10Nm


D
5



D
6



D
7



D
8



i

ARC300
Electrical
Settings

